Data Sheet
Fujitsu PRIMERGY TX150 S7 Mono-Socket Intel® Xeon® processor server

The one-processor tower server - maximized!

PRIMERGY TX tower servers are ideal for use in SMEs or branch offices. They increase operational efficiency by providing rock solid, record-breaking, energy efficient performance. That performance is built on 20-years of pioneering work in Green IT. As a customer, you benefit from a reduction in your organization's environmental impact and lower running costs. The reliability is proven by testing the machines through 5000 boot cycles – far more than other vendors do. PRIMERGY TX servers are also easy to manage via the PRIMERGY ServerView Suite, reducing IT admin workload and costs. Plus, tower to rack conversion kits are available for most TX systems, ensuring investment protection.

PRIMERGY TX150 S7

The PRIMERGY TX150 S7: the right system for SMEs or non-mission-critical decentralized infrastructures where the main focus is on expandability and availability. The expandability and availability come from the 6 expansion slots (5 of which PCIe Gen 2) and up to 8x 2.5 hot-plug hard disks. Increase the system's availability and energy efficiency through the use of optional redundant power supplies boasting up to 89% energy efficiency. The TX150 S7 also offers up to the latest generation Intel® Xeon® processor 3400 series single processor platform, delivering excellent energy-efficient performance at an attractive price. The PRIMERGY TX150 S7: the one processor tower server – maximized!

Features & Benefits

Main Features	Benefits
■ By combining the latest Intel® mono-processor platform and SAS 2.0 hard disks with Fujitsu's engineering, you can get great performance with low energy consumption	■ High performance and energy efficiency
■ Hot plug hard disks: choose between max. 4x 3.5-inch or max. 8x 2.5-inch. Power supply units: choose between standard or redundant	■ High availability options to suit your business
■ Up to 32 GB of RAM and 6 expansion slots (5 of which second generation PCIe slots)	■ High expandability - the TX150 S7 grows with your business
■ The PRIMERGY TX150 S7 can be integrated into a rack infrastructure with the tower to rack conversion kit	■ High versatility - increases your investment's lifetime
■ The green touch points, the system ID card and the customer self-service module make servicing the TX150 S7 easier	■ High serviceability - saves your time

Technical details

PRIMERGY TX150 S7						
Housing types	Tower	Microtower	Tower	Tower	Rack	Rack
Storage drive architecture	4x 3.5-inch SAS/ SATA	4x 3.5-inch SAS/ SATA	8x 2.5-inch SAS/ SATA/SSD	8x 2.5-inch SAS/ SATA/SSD	4x 3.5-inch SAS/ SATA	8x 2.5-inch SAS/ SATA/SSD
Power supply	Standard	Hot-plug	Standard	Hot-plug	Hot-plug	Hot-plug

Mainboard	
Mainboard type	D 2759
Chipset	Intel® 3420
Processor quantity and type	1 x Intel® Core™ i3 processor / Intel® Pentium® processor / Intel® Xeon® processor L3400 series / Intel® Xeon® processor X3400 series
Processor	Intel® Core™ i3-540 processor (2C/4T, 3.06 GHz, TLC: 4 MB, Turbo: No, 1333 MHz, 73 W)
	Intel® Pentium® processor G6950 (2C, 2.80 GHz, TLC: 3 MB, Turbo: No, 1066 MHz, 73 W)
	Intel® Xeon® processor L3426 (4C/8T, 1.86 GHz, TLC: 8 MB, Turbo: 2/2/9/10, 1333 MHz, 45 W)
	Intel® Xeon® processor X3430 (4C/4T, 2.40 GHz, TLC: 8 MB, Turbo: 1/1/2/3, 1333 MHz, 95 W)
	Intel® Xeon® processor X3440 (4C/8T, 2.53 GHz, TLC: 8 MB, Turbo: 1/1/2/3, 1333 MHz, 95 W)
	Intel® Xeon® processor X3450 (4C/8T, 2.66 GHz, TLC: 8 MB, Turbo: 1/1/4/4, 1333 MHz, 95 W)
	Intel® Xeon® processor X3470 (4C/8T, 2.93 GHz, TLC: 8 MB, Turbo: 2/2/4/5, 1333 MHz, 95 W)
	Intel® Xeon® processor X3480 (4C/8T, 3.06 GHz, TLC: 8 MB, Turbo: 2/2/4/5, 1333 MHz, 95 W)
Memory slots	6
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	1 GB - 32 GB
Memory protection	ECC
Memory notes	For the following modules a maximum of 4 DIMMs can be configured: 4GB (quad-ranked) with 1066MHz, 8GB RDIMM, all UDIMM modules. Maximum configurable memory capacity: UDIMMs (max. 16GB) with all processors; RDIMMs (max. 32 GB) with Xeon CPUs only. The following modules can be configured 6x: 4GB (dual-rank) and 2GB (dual-rank).
Memory options	2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM
Interfaces	
USB ports	10 x USB 2.0 (3x front, 4x rear, 3x internal)
Graphics (15-pin)	1 x VGA
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC or system or shared
Serial 2 (9-pin)	1 x serial RS-232-C (optional)
LAN / Ethernet (RJ-45)	1 x Gbit/s Ethernet
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port

Onboard or integrated Controller	
RAID controller	Integrated RAID 0/1 or RAID 5/6 controller for SAS base units (option, occupies one PCIe slot). additional RAID controller options are described under Components RAID controller
SATA Controller	Intel® 3420 Ibex Peak PCH Platform Control Hub, 2 ports used for accessible drives 4 port for internal SATA HDDs with RAID 0, 1, 10 for Windows and Linux;
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / 1.2 (option)
Slots	
PCI-Express 2.0 x1 (mech. x4)	2 x short
PCI-Express 2.0 x4 (mech. x8)	1 x Low profile ready, full height, long 3,3 V
PCI-Express 2.0 x8	2 x short 3,3V
PCI-slots	1 x PCI 32/33 MHz, 1x long, 5V
Slot Notes	in SAS configuration 1x PCI-Express occupied by modular RAID controller.
Drive bays	
Storage drive bay configuration	4x 3.5-inch, for SAS / SATA or 8x 2.5-inch for SAS/SATA/SSD optional
Accessible drive bays	3 x 5.25/1.6-inch
Notes accessible drives	all possible options described in relevant system configurator
Number of fans	1
Fan configuration	1 standard fan
Operating panel	
Operating buttons	On/off switch NMI button Reset button
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Panel (LSP) ServerView Local Service Display (LSD)
BIOS	
BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Server® 2012 Foundation
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows Server® 2008 R2 Foundation
	Microsoft® Windows® Web Server 2008 R2
	Microsoft® Windows® Small Business Server Essentials 2011
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows® Small Business Server 2008 Standard
	Microsoft® Windows® Small Business Server 2008 Premium
	Microsoft® Windows Server® 2003 Enterprise Edition
	Microsoft® Windows Server® 2003 Standard Edition
	Microsoft® Windows Server® 2003 Web Edition
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	VMware vSphere™ 4.1
	VMware vSphere™ 4.1 Embedded
	VMware vSphere™ 4.1 Installable
	VMware vSphere™ 4.0
	VMware vSphere™ 4.0 Embedded
	VMware vSphere™ 4.0 Installable
	Novell® SUSE Linux Enterprise Server 11
	Novell® SUSE Linux Enterprise Server 10
	Novell® SUSE Linux Enterprise Server 10 with XEN
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
	Red Hat® Enterprise Linux 5 with XEN
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
Operating system notes	Support of other Linux derivatives on demand

Server Management	
Standard	ServerView Suite - Deploy SV Installation Manager SV Scripting Toolkit SV Deployment Manager (30-day trial version) ServerView Suite - Control SV Operations Manager incl. PDA and ASR & R (Prefailure and Analysis; Automatic Server Recovery and Restart) SV Performance Management SV Power Management SV RAID Manager ServerView Suite - Maintain SV Remote Management (iRMC) SV Update Management (BIOS, Firmware, Windows Drives and SV Agents) SV Asset Management SV Online Diagnostics ServerView Suite - Integrate SV Integration packs e.g. for Microsoft System Center, Nagios, HP, SIM, HP NNM, IBM Tivoli, Altiris Deployment Solutions and others
Option	ServerView Suite - Deploy SV Deployment Manager (full version) ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR) and Remote Storage ServerView Suite - Integrate SV Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.

Dimensions / Weight	
Floor-stand (W x D x H)	205 x 584 x 444 mm
Rack (W x D x H)	482 x 570 x 220 mm
Dimension notes	Floorstand Width 306 mm with tilt protection; depth measured excludes handles on redundant PSU. Rack depth excludes handles of redundant PSU and rack front.
Height Unit Rack	5 U
Weight	21-28 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

Dimensions / Weight / Environmental (Base unit specific)	

Environmental	
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	SATA: 24 dB(A) idle mode/ 25 dB(A) operation mode; SAS: 31 dB(A) idle mode/ 33 dB(A) operation mode
Sound power (LWAd; 1B = 10dB)	SATA: 4.2 B idle mode/ 4.2 B operation mode ; SAS: 4.9 B idle mode/ 5.1 B operation mode
Noise notes / description	May vary according to configuration

Electrical values	
Power supply configuration	Base unit specific: 1x standard power supply or1x hot-plug power supply or 2x hot plug power supply for redundancy
Standard power supply output	350W (85% efficiency)
Hot-plug power supply output	450W (89% efficiency)
Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 240 V

Electrical values	
Rated frequency range	47 Hz - 63 Hz
Rated current max.	6A - 3A The rated current in basic configuration values are pending confirmation.
Rated current in basic configuration	1.9 A - 0.8 A
Active power (min. configuration)	80 W
Active power (max. configuration)	258 W
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: http://configurator.ts.fujitsu.com/public/
Apparent power (max. configuration)	81 VA - 258 VA (max. active power and max. apparent power values are configuration dependent) VA
Heat emission	928.8 kJ/h (880.3 BTU/h)

Energy Star ® 1.0 certified configurations

The following Energy Star Familiy configuration options use less energy and reduce greenhouse gas emissions:

PRIMERGY TX150 S7 E-StarFam1 (Dual-Core CPUs with standard PSU)
PRIMERGY TX150 S7 E-StarFam2 (Quad-Core CPUs with hot plug PSU)

http://ts.fujitsu.com/products/standard_servers/e_efficient.html

Compliance	
Germany	TÜV GS
Europe	CE Class A * CE label according to EU directives: Low-Voltage Directive 2006/95/EC, Electromagnetic Compatibility 2004/108/EC EN 300386 EN 50371 EN 55022 EN 55024 EN 60950 - 1 EN 61000-3-2 JEIDA EN 61000-3-3
USA/Canada	CSAc/us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Japan	VCCI Class A + JIS 61000-3-2
Russia	GOST-R
China	CCC (G 4943/ GB 9245 / GB 17625)
Australia/New Zealand	C-Tick (AS / NZS CISPR 22 Class A)
Taiwan	BSMI Class A (CNS 13438, CNS 14336) CNS 13436
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. Additional compliance with: Kenya:KEBS; Kuwait: KUCAS; Nigeria:SONCap; South Africa:SABS; Belarus: STB; Kazahkstan: GOST-K; Ukraine: SEMPRO * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://sp.ts.fujitsu.com/sites/certificates/

Components

Storage disks	SSD SATA, 6 Gb/s, 400 GB, MLC, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 200 GB, MLC, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 100 GB, MLC, hot-plug, 2.5-inch, enterprise
	HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 6 Gb/s, 250 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 3 Gb/s, 320 GB, 5400 rpm, hot-plug, 2.5-inch, economic
	HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 3 Gb/s, 160 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 3 Gb/s, 160 GB, 5400 rpm, hot-plug, 2.5-inch, economic
	HDD SATA, 3 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SAS, 6 Gb/s, 900 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 600 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 600 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
Backup Drives	DDS Gen5, 36 GB, 3 MB/s, half height, USB 2.0
	DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
	LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s
	LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s
	LTO5HH Ultrium, 1500 GB, 140 MB/s, half height, SAS 6Gb/s
	RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0
	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I
SCSI / SAS Controller	SAS Ctrl. 6 Gbit/s 8 ports ext. PCIe Gen2 x8
RAID Controller	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
	RAID 0/1 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 0/1 (D2607), 8 ports int. RAID level: 0, 1, 10, No BBU support (based on LSI SAS2008)
	Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, No BBU support (based on LSI 1068e)
	Integrated RAID 0/1 Ctrl., SAS/SATA 3 Gbit/s, 4 ports int. RAID level: 0, 1, 1E, No BBU support (based on LSI 1064e)

Communication, Network	Ethernet Ctrl. 1 x 1 Gbit/s PCIe x1 (Intel®)
	Ethernet Ctrl. 1 x 1 Gbit/s PCIe x4 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe x8 (Fujitsu)
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe x4 (Fujitsu)
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe x4 (Fujitsu)
Graphics add on cards	NVIDIA® Quadro® NVS 300, PCIe x1, 2x DVI/VGA
Rack infrastructure	Cable Arm 2U for 3rd party racks
	Rackmount kit full extraction (760mm), tool less mounting
	Cable Management for 19-inch DataCenter / PRIMECENTER Racks

Warranty	
Standard Warranty	1 year
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Service Lifecycle	5 years after end of product life (new, refurbished or functionally identical parts)
Service Weblink	http://www.fujitsu.com/fts/services

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX150 S7, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX150 S7, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2012-12-05 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions